

MIFARE Classic + Prox card - 350 / 355 / 1431 / 1441 / 1437 / 1447

Encompasses the industry's broadest range of open standard contactless smart card products. Provides the memory structure and capacity to store multiple applications on a single credential with the addition of Proximity technology for easier migration. All MIFARE Classic + Prox cards can be ordered with or without SIO encoding.

Ensure each required option has been checked with the appropriate choice to fulfill a completed order form.

MIFARE Classic + Prox card with SIO encoding (Recommended)

OR

MIFARE Classic + Prox card without SIO encoding

- ☐ 3500 (1K) Standard PVC
- ☐ 3506 (4K) Standard PVC
- ☐ 3550 (1K) Composite 40% Polyester/PVC*
- ☐ 3556 (4K) Composite 40% Polyester/PVC*

- ☐ 1431 (1K) Standard PVC
- ☐ 1441 (4K) Standard PVC
- ☐ 1437 (1K) Composite 40% Polyester / PVC*
- ☐ 1447 (4K) Composite 40% Polyester / PVC*

Programming (Select one option)

- ☐ P - Programmed with Security Identity Object (SIO) for MIFARE
- ☐ R - Both interfaces programmed (MIFARE with Security Identity Object (SIO), Prox programmed with HID format)
- ☐ V - Unprogrammed SIO, for use with iCLASS SE Encoder, Prox unprogrammed

Programming (Select one option)

- ☐ L - Programmed, (125 kHz only with HID Format)⁶.
Specify Programming Information.
- ☐ M - Programmed, HID MIFARE ⁶ (Specify HID format, for example H10301).
- ☐ B - Programmed, (125kHz and 13.56 MHz with HID Format)⁶.
Specify Programming Information.
- ☐ N - Non-Programmed (125 kHz & 13.56 MHz without HID Format)⁶.
Programming Information Not Required.
- ☐ S - Custom Programmed, (13.56 MHz only)⁶, Prox configured
Specify Programming Information

Front Packaging (Select one option)

- ☐ G - Plain White with Gloss Finish
- ☐ C - Custom Artwork with Gloss Finish - Specify Custom Artwork Number¹

Back Packaging (Select one option)

- ☐ G - Plain White with Gloss Finish²
- ☐ 1 - Plain White with Gloss Finish with Magnetic Stripe²
- ☐ C - Custom Artwork with Gloss Finish - Specify Custom Artwork Number^{1, 2}
- ☐ 3 - Custom Artwork with Gloss Finish with Magnetic Stripe - Specify Custom Artwork Number^{1, 2}

13.56 MHz MIFARE Card Numbering³ (Select one option)

- ☐ M - Sequential Matching Encoded/Printed (Inkjetted)⁵
- ☐ N - No Printed Card Numbering
- ☐ U - UID (CSN) HEX card numbering only (Inkjetted)⁵
- ☐ V - UID (CSN) Decimal card numbering only (Inkjetted)⁵
- ☐ S - Sequential Encoded/Sequential Non-Matching Printed (Inkjetted)⁵
- ☐ R - Random Encoded/Non-Matching Sequential Printed (Inkjetted)⁵
- ☐ A - Sequential Matching Encoded/Printed (Laser Engraved)⁴
- ☐ B - Sequential Encoded/Sequential Non-Matching Printed (Laser Engraved)⁴
- ☐ C - Random Encoded/Non-Matching Sequential Printed (Laser Engraved)⁴
- ☐ Z - Reversed UID (CSN) Decimal card numbering only (Laser Engraved)⁴

Slot Punch (Select one option)

- ☐ N - No slot punch. This card can be slotted vertically, Printed Vertical Slot Indicators
- ☐ V - Vertical Slot Punch

125 kHz Proximity Card Numbering³ (Select one option)

- ☐ M - Sequential Matching Encoded/Printed (Inkjetted)
- ☐ N - No Printed Card Numbering
- ☐ S - Sequential Encoded/Sequential Non-Matching Printed (Inkjetted)
- ☐ R - Random Encoded/Non-Matching Sequential Printed (Inkjetted)
- ☐ A - Sequential Matching Encoded/Printed (Engraved)⁴
- ☐ B - Sequential Encoded/Sequential Non-Matching Printed (Engraved)⁴
- ☐ C - Random Encoded/Non-Matching Sequential Printed (Engraved)⁴

Option - Custom Artwork¹

- ☐ _____ (Specify Artwork Number - Refer to the Custom Artwork forms for new artwork)

Enter your final card options from check boxes above. Example: 3506PGGMNS

Final Part Number						N			-	(Options #)
-------------------	--	--	--	--	--	---	--	--	---	-------------

13.56 MHz Card Programming Information

